

Lynx

Opaque Ultra

Lynx® Opaque Ultra Product Specifications

Basis Weight Text / Bond / Cover 25 x 38 / 17 x 22 / 20 x 26	GSM	Brightness GE	OPACITY		SMOOTHNESS			CALIPER		
			Super Smooth	Smooth & Vellum	Super Smooth	Smooth	Vellum	Super Smooth	Smooth	Vellum
35 T	52	96	—	86	—	120	—	—	2.7	—
40 T	59	96	—	89	—	120	200	—	3.1	3.4
50/20 T	74	96	—	93	—	140	230	—	3.8	4.3
60/24 T	89	96	93	95	70	140	230	4.2	4.6	5.0
70/28 T	104	96	94	96	70	140	230	4.7	5.2	5.8
80/32 T	118	96	96	96	70	130	230	5.4	6.1	6.9
100/40 T	148	96	97	97	70	130	—	6.7	7.7	—
65 C	176	96	98	98	70	130	—	8.0	8.8	—
80 C	216	96	99	99	70	130	—	10.0	11.0	—
100 C	270	96	99	99	90	130	—	12.0	14.1	—
120 C	325	96	99	99	90	130	—	14.5	16.0	—

Features:

- 96 brightness with a brilliant true-white shade
- Excellent opacity for minimal show-through
- Smooth, uniform surface for better resolution
- Consistent runnability on press
- Digital sizes available in the Lynx Digital product line
- Available in super smooth, smooth, and vellum.

Environmental Characteristics:



- Forest Stewardship Council® (FSC®) certified by NEPCo
- Sustainable Forestry Initiative® (SFI®) Certified Sourcing
- Made with Total Chlorine Free (TCF) and Elemental Chlorine Free (ECF) virgin fiber content
- Available with 10% or 30% PCW (50# text to 100# cover only)
- Manufactured under alkaline (acid-free) conditions for increased longevity and performance

Product Benefits:

- Value alternative to coated sheets
- Ability to mix and match finishes within the Lynx Opaque Ultra Brand
- Mini press ready skids with a maximum skid height of 45" for improved printing cost efficiencies
- Available next day through our superior service profile

Ideal For:

- Brochures
- Direct mail
- Annual reports
- Financial printing

