

# Domtar POS 57L - 2.6



## Product Specifications

Caliper	Basis Weight	Brightness (UV Included)	Thermal Response - Nominal				Gurley Stiffness Nominal (mg)		Elmendorf Tear Nominal (g)		Parker Print Surf
			Static - (°C ± 5°)		Dynamic - Atlantek 400 (mJ/mm <sup>2</sup> )		MD:	CD:	MD:	CD:	
			0.2 ODU	91	0.2 ODU	4.8					
mils	17 x 22— 500 (lbs)	>85	0.2 ODU	91	0.2 ODU	4.8	42	20	37	43	<2.00
2.60 2.45 - 2.75	14.6 13.8 - 15.4		1.0 ODU	132	1.0 ODU	9.2					
µm	g/m <sup>2</sup>		Max. Density	1.26	Max. Density	1.53					
66.0 62.2 - 69.8	54.9 51.9 - 57.9		Required Temp.	149	Energy Req.	16.0					

### Features:

- Good for general imaging
- 10 years image life, 3 years storage life (under proper storage conditions for thermal paper)


### Environmental Characteristics:

- Produced without the use of bisphenol A (BPA)

### Ideal For:

- Economy point-of-sale for retail use
- Printer
- Facsimile
- Calculator
- Parking receipts
- ATM receipts
- Gas pump receipts

**Dynamic Sensitivity**



**Static Sensitivity**

