



LynxJET® Dye Specifications

Basis Weight (17 x 22)	GSM	Brightness	Opacity	Smoothness	Caliper	Length Target (+/-200 linear feet) 40"/3"	Length Target (+/-200 linear feet) 50"/3"
20	75	96	92	130	3.8	26,700	41,500
24	90	96	94	130	4.6	22,600	35,000
28	105	96	96	130	5.2	19,900	30,800

Product Features

- Designed for today's most advanced dye high speed inkjet systems
- Surface treatment specifically engineered for improved print quality when used on dye based systems greater lifts in density and depth of color
- High brightness and true white shade for enhanced graphics & sharp contrast
- · High opacity for minimal side to side show-through
- Consistent runnability on press and in post-processing equipment for inserting, punching and folding

Common Uses

- · Direct mail
- Statements
- Transpromotional documents
- Transpromotional postcards
- · Transactional business return cards

Environmental Characteristics (Acid-Free



- Forest Stewardship Council® (FSC®) Certified
- Sustainable Forestry Initiative® (SFI®) Certified Sourcing
- Made with Elemental Chlorine Free (ECF) virgin fiber content
- Manufactured under alkaline (acid-free) conditions for increased longevity and performance



Domtar Performance Commitment

Domtar's digital and inkjet products are designed and recommended for digital and inkjet production presses, desktop printers (laser and inkjet) and copiers within the limitations specified by the original equipment manufacturer.

We partner with leading OEM's to print test and certify our inkjet products as fit for use on a wide variety of equipment. Domtar's products are optimized for runnability on press and through post-processing. Our surface treatment will enhance print quality compared to untreated stocks when using dye inks. As always, Domtar stands behind our commitment and our products.





